



SKJERVEN
MORRILL
MACPHERSON LLP

09-29-00

A

Docket No.: M-9579 US

09/28/00
jc930 U.S. PTO

September 28, 2000

jc914 U.S. PTO
09/28/00
09/672644

Box Patent Application
Commissioner For Patents
Washington, D. C. 20231

Enclosed herewith for filing is a patent application, as follows:

Inventor(s): Koyama, Tetsu; Peng, Jason; Cohen, Paul E.;

Title: Four Dimensional Equalizer And Far-End Cross Talk Canceler in Gigabit Ethernet Signals

X Return Receipt Postcard
X This Transmittal Letter (in duplicate)
12 page(s) Specification (not including claims)
3 page(s) Claims
1 page Abstract
0 Sheet(s) of Drawings
3 page(s) Declaration For Patent Application and Power of Attorney (unsigned)

CLAIMS AS FILED

For	Number Filed		Number Extra		Rate		Basic Fee
Total Claims	7	-20 =	0	x	\$18.00	=	\$ 0.00
Independent Claims	1	-3 =	0	x	\$78.00	=	\$ 0.00
<input type="checkbox"/>	Fee of _____ for the first filing of one or more multiple dependent claims per application						\$
<input type="checkbox"/>	Fee for Request for Extension of Time						\$

Please make the following charges to Deposit Account 19-2386:

- ☒ Total fee for filing the patent application in the amount of \$ 690.00
☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account 19-2386.

EXPRESS MAIL LABEL NO:

EL708269469US

Respectfully submitted,

Mary Jo Bertani

Mary Jo Bertani
Attorney for Applicants
Reg. No. 42,321

"Express Mail" mailing label number:

EL708269469US

Four Dimensional Equalizer and Far-End Cross Talk Canceler in Gigabit Ethernet Signals

Tetsu Koyama
Jason Peng
Paul E. Cohen

5

Background of the Invention

Field of the Invention

10 This invention relates generally to noise reduction in communication networks. More specifically, this invention relates to simultaneously removing far-end cross talk and inter-symbol interference from signals transmitted over an N-dimensional communication network.

Description of the Related Art

15 Insatiable demand for bandwidth in LAN applications has motivated the evolution of high-speed 1000BASE-T Ethernet from its predecessors, such as Fast Ethernet 100BASE-T and 10BASE-T.

20 In order to achieve the high throughput of Gigabit Ethernet, impairments such as cable attenuation, echo, near-end cross talk (NEXT), and far-end cross talk (FEXT) over the cable channel(s) must be reduced as much as possible. Another source of errors in baseband communication systems is intersymbol interference (ISI) arising from the dispersive nature of the communications channel, i.e. pulse distortion arising from the non-ideal filtering characteristics of the transmission channel leading to interference between symbols.

Attenuation, echo, and NEXT can be controlled through the use of a linear equalizer, a decision feedback equalizer (DFE), echo cancelers, and NEXT cancelers. However, none of these conventional components removes FEXT noise.

It is nonetheless desirable to reduce errors introduced in transmitted signals from ISI and FEXT. Although the magnitude of FEXT noise is usually much smaller than NEXT interference, any reduction of FEXT can only improve the performance of a Gigabit Ethernet Transceiver, as well as other communication networks having similar impairments. It is also true that if FEXT and ISI is removed, then the resulting Gigabit Ethernet Transceiver may be usable with cable that is either longer or of inferior quality than specified by industry standards.

Summary of the Invention

In one embodiment, a multidimensional equalizer and cross talk canceler for a communication network is provided that simultaneously removes far end cross talk (FEXT) and intersymbol interference (ISI) from a received signal. A multidimensional channel is treated as a single multidimensional channel and a receiver in the communication network equalizes received signals through the use of the multidimensional equalizer. A multidimensional equalizer and cross talk canceler for a communication network that simultaneously removes far end cross talk (FEXT) and intersymbol interference (ISI) from a received signal. A multidimensional-pair channel is treated as a single multidimensional channel and a receiver in the communication network equalizes received signals through the use of the multidimensional equalizer. A decision feedback equalizer determines a multidimensional steepest descent gradient to adjust matrix coefficients that are proportional to estimates of

$$\frac{\partial e_n}{\partial Q_k^{i,j}}, \text{ wherein } Q_k^{i,j} \leftarrow \left(Q_k^{i,j} - \mu \cdot \left(\frac{\partial e_n}{\partial Q_k^{i,j}} \right) \right)$$

and

$$\frac{\partial e_n}{\partial Q_k^{i,j}} = 2 \cdot (Z_n^i - X_{n-p}^i) \cdot Y_{n-k}^j.$$

The equalizer includes:

a vector data unit delay operator that passes the received data vector Y_n through a series of unit delay operators to generate successive tap input data Y_n, Y_{n-1}, Y_{n-2} ;

5 a first matrix multiplication operator that receives a $1 \times N$ matrix Y_{n-k} from the unit delay operator and multiplies it with the $N \times 1$ matrix of scaled vector error data $(Z_n - X_n)$ to generate a $N \times N$ adjustment matrix;

a matrix summation operator that adds the adjustment matrix to a Q_{n-k} tap matrix and outputs a corrected tap matrix Q_{n-k+1} ;

10 matrix tap unit delay operator that receives the corrected tap matrix Q_{n-k+1} , and introduces a one cycle delay to generate a Q_{n-k} tap matrix; and

a second matrix multiplication operator that multiplies the Q_{n-k} tap matrix from the matrix tap unit delay operator by the Y_{n-k+1} vector from the vector data unit delay operator.

15 The multidimensional equalizer and cross talk canceler of the present invention exhibits significantly better noise margin compared to multiple scalar equalizers and advantageously permits the use longer cable runs or the use of physical channels that are in some way inferior.

20 The foregoing has outlined rather broadly the objects, features, and technical advantages of the present invention so that the detailed description of the invention that follows may be better understood.

Brief Description of the Drawings

Figure 1 is a diagram of a generic communication channel between a transmitter and a receiver.

25 Figure 1a is a diagram of components typically included in a four channel Gigabit Ethernet network.

Figure 2 is a block diagram of a receiver for signals in an Ethernet network.

Figure 2a is a block diagram of a receiver for signals in an Ethernet network in accordance with the present invention.

Figure 3 is a block diagram of a single tap of a one dimensional equalizer known in the prior art.

5 Figure 4 is a block diagram of a single tap of a four dimensional equalizer and far end cross talk canceller in accordance with the present invention.

Figure 5a is a graph of the signal to noise ratio versus convergence time in a four dimensional equalizer in accordance with the present invention.

10 Figure 5b is a graph of the signal pattern versus convergence time in a four dimensional equalizer in accordance with the present invention.

Figure 6a is a graph of the signal to noise ratio versus convergence time in a conventional one dimensional equalizer known in the prior art.

15 Figure 6b is a graph of the signal pattern versus convergence time in a four dimensional equalizer known in the prior art.

The present invention may be better understood, and its numerous objects, features, and advantages made apparent to those skilled in the art by referencing the accompanying drawings. The use of the same reference symbols in different drawings indicates similar or identical items.

20 **Detailed Description**

Fig. 1 shows a generic model of a baseband transmission system 10. An incoming binary sequence $\{b_k\}$ of symbols 0 and 1, each of duration T_b is transformed by the pulse amplitude modulator 12 into a sequence of short pulses $\{a_k\}$ of amplitudes +1 and -1. These short pulses are applied to a transmit filter 14 of impulse

response $g(t)$ producing the transmitted signal $X(t)$. Note that in 1000BASE-T over a copper channel, the signals on each wire pair are not just 0 or 1, but rather, five different voltage levels (0, ± 1 and ± 2) are applied.

The signal $X(t)$ is modified by transmission through a channel 16 of impulse response $h(t)$ and also has some noise $n(t)$ added to it, producing noisy signal $Y(t)$. At receiver 18, the noisy signal $Y(t)$ is passed through a receiver equalizer 20 and the resulting filtered output $Z(t)$ is synchronously sampled at intervals of T_b . The samples, $Z(T)$, are passed to a threshold decision device 22, which outputs a 1 if the sample is greater than the threshold 1, and 0 if less than the threshold.

Referring now to Fig. 1a, an Ethernet network 100 capable of full-duplex 4-channel communication over a copper medium includes four twisted pair cables 102, 104, 106, 108. One (1) gigabit per second (Gb/s) throughput is achieved using eight transceivers (four at each end) 110 through 124 as shown in Figure 1a. Each transceiver 110 through 124 achieves throughput of 250 Mb/s, but operates at approximately 290 Mb/s to accommodate coding and signaling overhead.

Hybrids in transceivers 110 through 124 separate transmit and receive signals on each wire pair. The transmitters (denoted by "TX" in Fig. 1) in transceivers 110 through 124 perform the relatively simple task of outputting packets of data that include the address of a destination receiver. Data received by the receivers in transceivers 110 through 124 is subject to errors due to cable attenuation, echo from the transmitter, near-end cross talk (NEXT) from one or more adjacent transmitters, and far-end cross talk (FEXT) from transmitters at the other end of the cable.

Crosstalk is unwanted signals coupled between adjacent wire pairs. Each two-wire pair is affected by crosstalk from the adjacent three pairs. Crosstalk is characterized in reference to the transmitter. NEXT is crosstalk that appears at the output of a wire pair at the transmitter end of the cable. FEXT is crosstalk that appears at the output of a wire pair at the far end of the cable from the transmitter. For example, the receiver in transceiver 110 may be subject to NEXT from

transmitters in transceivers 112, 114, and 116, while the receivers in transceivers 110, 112, 114, and 116 may be subject to FEXT from transceivers 118, 120, 122 and 124.

Referring now to Fig. 2, receiver 200 receives data, denoted Y_n . When a signal, X_n is applied to a channel, ideally it is transmitted only to the far end of that channel (i.e., travels in only one direction). In practice, part of the signal is reflected back toward the transmitter due to impedance discontinuities within the channel. The amount of signal reflected back is characterized by return loss. The greater the return loss, the less the signal is reflected. Return loss becomes more significant at elevated frequencies. To reduce or eliminate errors in transmission, the reflected signal must be small compared to the desired receive signal at all relevant frequencies. Since the desired receive signal is coming from the far end of the cabling, it has been reduced in size by the attenuation of the cabling. The amount of undesired reflected signal may quickly exceed the desired receive signal as frequency increases. This is unacceptable for error free transmission.

The effects of the undesired reflected signal is substantially reduced using known digital return loss cancellation, also referred to as "echo cancellation," techniques in echo canceller 204. In the known techniques, echo canceller 204 predicts the amplitude and echo response as a function of time. The digital "taps" of a delay line filter are adjusted accordingly, and the predicted echo response is subtracted from the total incoming receive signal to "cancel" the effect of the echo. More specifically, a portion of the signal transmitted from the transceiver end is subtracted, a portion of the previous bit transmitted from the transceiver end is subtracted, a portion of the bit before, etc. The magnitude of the portion subtracted is stored in digital delay line "taps." It should be noted that the echo is uncorrelated to the desired signal coming from the other end of the cabling. By slowly adjusting the taps, the echo canceller will track only the echo, thus avoiding cancelling the desired receive signal.

NEXT canceller 206 uses techniques similar to echo canceller 204 to cancel noise due to near end cross talk. The correlation between the transmit signal applied to one pair and the receive signal on another pair can be determined in terms of

magnitude and time delay. Since each receive pair is corrupted with near-end crosstalk noise from three other pairs, each receiver requires its own NEXT canceller 206.

Attenuation refers to the situation where the amplitude of a signal diminishes as it travels down the length of the cable. High frequency signals (the sharp edges of digital pulses) are attenuated more than low frequency signals and this results in distortion or jitter unless it is compensated.

Equal level far-end crosstalk (ELFEXT) is FEXT with the cable attenuation removed to provide equal-level comparisons, i.e., crosstalk and receive signals voltages are compared at the end of the cabling opposite the transmitter. Signal equalization compensates for signal distortion introduced by the communication channel 16 (Fig. 1). As noted previously, broadband signals are distorted as they pass along the line, causing inter-symbol-interference (ISI). Receiving signals with large ISI is difficult because the receiver 200 cannot tell the difference between the current symbol and the previous one.

To compound the problem, feed-forward equalizer 208 increases ISI as it whitens noise. Unlike feed-forward equalizer 208, decision-feedback equalizer (DFE) 210 does not modify the noise. Therefore, DFE 210 is used to clean up the ISI generated by the channel 202 and the feed-forward equalizer 208. Feed forward equalizer 208 typically includes a finite impulse response (FIR) filter. DFE 210 includes a feedback equalization filter and provides better signal equalization than feed forward equalizer 208 alone, especially when the transmission medium introduces strong signal attenuation within specific frequency regions.

Referring now to Fig. 2a, in one embodiment, the present invention provides a four dimensional DFE (4D-EQLFXC) 212 that efficiently reduces FEXT and ISI by simultaneously equalizing the input signal and cancelling FEXT in the four receivers.

Receiver 200 detects the signal Y_n at time n . The 4D-EQLFXC 212 of the present invention reduces the effects of ISI and FEXT among each of the four

channels 202 and includes feed forward equalizer 208 and 4D-EQLFXC 212 that operate on the $\{Y_n\}$ sequence to determine an estimate of $\{Z_n\}$ and $\{X_n\}$. It is assumed that feed forward equalizer 208 can be constructed in the form

$$Z_n = \sum_{k=0}^N Q_k \cdot Y_{n-k} , \text{ (N: tap length)}$$

- 5 The higher the number of taps that are used, the more noise reduction is achieved, however, a higher number of taps increases power consumption and expense. Therefore, simulations are used to determine the number of taps required to achieve acceptable noise reduction.

- 10 For a four dimensional system, i.e., four channels, X_n , Y_n , and Z_n are four column (channel) vectors, whose coordinates are referenced with superscripts. That is,

$$X_n = \langle X_n^1, X_n^2, X_n^3, X_n^4 \rangle$$

$$Y_n = \langle Y_n^1, Y_n^2, Y_n^3, Y_n^4 \rangle$$

$$Z_n = \langle Z_n^1, Z_n^2, Z_n^3, Z_n^4 \rangle$$

- 15 and Q_k in general is a 4x4 symmetric matrix representing one tap matrix of 4D-EQLFXC coefficients. There is one tap matrix for each tap; each tap matrix has size $K \times K$ where K is the number of channels. Superscripts are again used to designate individual entries.

$$Q_k = \begin{bmatrix} Q_k^{1,1} & Q_k^{1,2} & Q_k^{1,3} & Q_k^{1,4} \\ Q_k^{2,1} & Q_k^{2,2} & Q_k^{2,3} & Q_k^{2,4} \\ Q_k^{3,1} & Q_k^{3,2} & Q_k^{3,3} & Q_k^{3,4} \\ Q_k^{4,1} & Q_k^{4,2} & Q_k^{4,3} & Q_k^{4,4} \end{bmatrix}$$

- 20 The error, e_n , is defined as the distance between Z_n and X_n , which can be determined as follows:

$$e_n = \|Z_n - X_{n-p}\|^2 = \left(\sum_{i=1}^4 (Z_n^i - X_{n-p}^i)^2 \right).$$

Where p is an integer greater than or equal to 0, and e_n is defined as the distance between Z_n and X_{n-p} . Typically, $p = (N+1)/2$ if N is odd, or is chosen close to this value. Values for n, i, j and k are fixed, with $l = i, j = 4$, and $k = N$. Applying the least mean square (LMS) algorithm, an estimate of the gradient ∇_n with coordinates

5 $\frac{\partial e_n}{\partial Q_k^{i,j}}$ is determined as follows:

$$\begin{aligned}
 \frac{\partial e_n}{\partial Q_k^{i,j}} &= \frac{\partial}{\partial Q_k^{i,j}} \sum_{l=1}^4 (Z_n^l - X_{n-p}^l)^2 \\
 &= 2 \cdot \sum_{l=1}^4 (Z_n^l - X_{n-p}^l) \cdot \frac{\partial Z_n^l}{\partial Q_k^{i,j}} \\
 &= 2 \cdot \sum_{l=1}^4 (Z_n^l - X_{n-p}^l) \cdot \frac{\partial}{\partial Q_k^{i,j}} \sum_{k=0}^N \sum_{v=1}^4 Q_k^{l,v} \circ Y_{n-k}^v \\
 10 &= 2 \cdot (Z_n^i - X_{n-p}^i) \cdot Y_{n-k}^j
 \end{aligned}$$

Note that coordinates with $i = j$ relate to channel equalization while those with $i \neq j$ relate primarily to FEXT cancellation.

The present invention uses the steepest descent method to follow the gradient to an optimal solution. The gradient is a vector (in this case in a space of dimension
15 16N, where N is the number of taps) that points in the direction of maximum increase in the error function. An example of an adaptive steepest descent method for time instance $n+1$, is represented by:

$$Q_k^{i,j} \leftarrow \left(Q_k^{i,j} - \mu \cdot \left(\frac{\partial e_n}{\partial Q_k^{i,j}} \right) \right)$$

in which μ is a constant that regulates the step size.

20 The 4D-EQLFXC 212 initially assigns values to the matrices $\{Q_k : 1 \leq k \leq N\}$. For example, the values can each be set initially to the zero matrix except for the p^{th} matrix which is set to the identity matrix. For potentially faster convergence, the values can be preloaded by measuring the characteristics of typical channels, or alternatively, from the preceding training sequence.

During each cycle of equalizer training, the matrices are updated by a vector amount that is proportional to the gradient, as estimated using the partial derivatives of ε_n and e_n which are determined as shown hereinabove.

Note that Z_n^i and Y_{n-k}^j can be measured directly. During training, the X_n^i terms
5 are known to be either 0 or ± 2 and so can be determined with reasonable confidence. As previously noted, the computation involved in estimating these partial derivatives can be reduced by assuming that the Q_i are symmetric.

After the training period, the X_n^i terms are no longer known to be either 0 or ± 2 but they are still known to be 0, ± 1 or ± 2 , as specified in IEEE Std 802.3ab-1999,
10 in tables 40-1, 40-2 and section 40.3.1.3.6. Assuming that the channel impairments are largely removed, the X_n^i terms can still be determined with reasonable confidence. It can be beneficial to continue making the adjustments, although the adjustments can be made less aggressively, i.e., with a smaller constant μ of proportionality applied to the gradient.

15 The present invention for the 4D-EQLFXC 212 is similar to a one-dimensional least mean square equalizer (1D-EQL), but the present invention provides the additional advantage of canceling FEXT by performing vector operations instead of scalar operations used in a 1D-EQL. Each tap of 4D-EQLFXC coefficients becomes a 4 x 4 symmetric matrix instead of a scalar. The similarity of the tap
20 operation for the two equalizers is illustrated in Figures 3 and 4. The difference is that the 4D-EQLFXC in Figure 3 uses vector and matrix operations where the 1D-EQL in Figure 4 uses scalar operations.

Referring now to Figure 3, if all of the taps of the 4D-EQLFXC are considered together, the received data vector Y_n is passed through a series of Unit Delay operators
25 301 so that successive taps see as input data $Y_n, Y_{n-1}, Y_{n-2}, \dots$. Matrix Multiplication operator 303 receives the $1 \times N$ matrix Y_{n-k} matrix from unit delay operators 301 and multiplies it with the $N \times 1$ matrix of scaled vector error (gradient) data $(Z_n - X_n)$ from Vector Error Scaling operator 302. Matrix Summation operator 304 receives from

Matrix Multiplication operator 303 a $N \times N$ matrix of adjustments to the matrix Q_{n-k} . Matrix Summation operator 304 adds the adjustment to the Q_{n-k} matrix and outputs the corrected matrix, Q_{n-k} , to Matrix Tap Unit Delay operator 305. Matrix Tap Unit Delay operator 305 introduces a one cycle delay so that Q_{n-k} arrives at matrix Multiplication operator 306 a cycle later when Y_{n-k+1} arrives from Vector Data Unit Delay operator 306.

The performance of a simulated 4D-EQLFXC in accordance with the present invention is shown in Figures 5a and 5b, while the performance of a simulated 1D-EQL is shown in Figures 6a and 6b. In Figs. 5a and 6a, the results of the simulation shows the 4D-EQLFXC having an overall signal to noise ratio (SNR) advantage of 22 dB compared to the 1D-EQL. Note that the SNR is calculated on one result after subtraction between feed-forward equalizer 208 and decision-feedback equalizer 210, and another result after subtraction between the first result and the signal after decision circuits.

A 4D-EQLFXC is computationally more complex than four 1D-EQLs with the same number of taps, so using the same number of taps in each case could be viewed as an uneven comparison. But, the computational complexity, in either case, can be estimated as the number of coefficients that are updated each cycle.

In order to compare the two approaches on an even basis, the number of taps has been adjusted so that the 200 coefficients must be updated in each simulation. For the 4D-EQLFXC there are ten such coefficients per tap whereas for the four 1D-EQLs there are only four coefficients per tap. Since 20 taps are used for the 4D-EQLFXC, 50 taps are used for each 1D-EQL.

The 4D-EQLFXC of the present invention exhibits significantly better noise margin compared to multiple scalar equalizers and advantageously permits the use longer cable runs or the use of physical channels that are in some way inferior.

These present invention can be extended and generalized to provide an “N” dimensional EQLFXC for N-channel full-duplex communication and is applicable to other communications systems in addition to Ethernet networks.

While the present invention is described in the context of a communication
5 network, those skilled in the art will appreciate that the present invention is capable of being distributed as a program product in a variety of forms, and that the present invention applies equally regardless of the particular type of signal bearing media used to actually carry out the distribution. Examples of signal bearing media include:
recordable type media such as floppy disks and CD-ROM, transmission type media
10 such as digital and analog communications links, as well as other media storage and distribution systems.

Additionally, the foregoing detailed description has set forth various embodiments of the present invention via the use of block diagrams, flowcharts, and examples. It will be understood by those within the art that each block diagram
15 component, flowchart step, and operations and/or components illustrated by the use of examples can be implemented, individually and/or collectively, by a wide range of hardware, software, firmware, or any combination thereof. In one embodiment, the present invention may be implemented via Application Specific Integrated Circuits (ASICs). However, those skilled in the art will recognize that the embodiments
20 disclosed herein, in whole or in part, can be equivalently implemented in standard Integrated Circuits, as a computer program running on a computer, as firmware, or as virtually any combination thereof and that designing the circuitry and/or writing the code for the software or firmware would be well within the skill of one of ordinary skill in the art in light of this disclosure.

25 While the invention has been described with respect to the embodiments and variations set forth above, these embodiments and variations are illustrative and the invention is not to be considered limited in scope to these embodiments and variations. Accordingly, various other embodiments and modifications and improvements not described herein may be within the spirit and scope of the present
30 invention, as defined by the following claims.

WHAT IS CLAIMED IS:

1 1. An apparatus for canceling far end cross talk and intersymbol interference in
2 a communication network, the apparatus comprising:

3 a decision feedback equalizer operable to determine a multidimensional
4 steepest descent gradient to adjust matrix coefficients that are
5 proportional to estimates of

$$\frac{\partial e_n}{\partial Q_k^{i,j}}, \text{ wherein } Q_k^{i,j} \leftarrow \left(Q_k^{i,j} - \mu \cdot \left(\frac{\partial e_n}{\partial Q_k^{i,j}} \right) \right).$$

1 2. The apparatus as set forth in Claim 1, wherein:

$$\frac{\partial e_n}{\partial Q_k^{i,j}} = 2 \cdot (Z_n^i - X_{n-p}^i) \cdot Y_{n-k}^j.$$

1 3. The apparatus as set forth in Claim 1, further comprising:

2 a vector data unit delay operator coupled to receive an input vector Y_n from a
3 communication channel;

4 a vector error scaling operator for generating an error signal proportional to the
5 difference between the output Z_n of the feedforward equalizer and the
6 input X_n to the communication channel;

7 a first matrix multiplication operator coupled to multiply input from the vector
8 data unit delay operator and the vector error scaling operator;

9 a matrix summation operator coupled to add the output from the first matrix
10 multiplication operator to the output from a matrix tap unit delay
11 operator, wherein the matrix tap unit delay operator receives input from
12 the matrix summation operator; and

13 a second matrix multiplication operator coupled to multiply input from the
14 matrix tap unit delay operator and the vector data unit delay operator,
15 thereby generating .

1 4. The apparatus, as set forth in Claim 3, wherein:
2 the vector data unit delay operator passes a data vector Y_n through a series of
3 unit delay operators to generate successive tap input data Y_n, Y_{n-1}, Y_{n-2} .

1 5. The apparatus, as set forth in Claim 4, wherein:
2 the first matrix multiplication operator receives the $1 \times N$ matrix Y_{n-k} from the
3 unit delay operator and multiplies it with the $N \times 1$ matrix of scaled
4 vector error data $(Z_n - X_n)$ from the vector error scaling operator.

1 6. The apparatus, as set forth in Claim 3, wherein:
2 the matrix summation operator receives a $N \times N$ adjustment matrix from the
3 first matrix multiplication operator, adds the adjustment matrix to a
4 Q_{n-k} matrix from the matrix tap unit delay operator, and outputs a
5 corrected matrix Q_{n-k+1} .

1 7. The apparatus, as set forth in Claim 6, wherein:
2 the matrix tap unit delay operator receives the corrected matrix Q_{n-k+1} from the
3 matrix summation operator, and introduces a one cycle delay to
4 generate the Q_{n-k} matrix.

Four Dimensional Equalizer and Far-End Cross Talk Canceler in Gigabit Ethernet Signals

Tetsu Koyama
Jason Peng
Paul E. Cohen

Abstract of the Disclosure

A multidimensional equalizer and cross talk canceler for a communication network that simultaneously removes far end cross talk (FEXT) and intersymbol interference (ISI) from a received signal. A multidimensional-pair channel is treated as a single multidimensional channel and a receiver in the communication network equalizes received signals through the use of the multidimensional equalizer. A decision feedback equalizer determines a multidimensional steepest descent gradient to adjust matrix coefficients that are proportional to estimates of

$$\frac{\partial e_n}{\partial Q_k^{i,j}}, \text{ wherein } Q_k^{i,j} \leftarrow \left(Q_k^{i,j} - \mu \cdot \left(\frac{\partial e_n}{\partial Q_k^{i,j}} \right) \right)$$

and

$$\frac{\partial e_n}{\partial Q_k^{i,j}} = 2 \cdot (Z_n^i - X_{n-p}^i) \cdot Y_{n-k}^j.$$

The equalizer includes:

- a vector data unit delay operator that passes the received data vector Y_n through a series of unit delay operators to generate successive tap input data Y_n, Y_{n-1}, Y_{n-2} ;
- a first matrix multiplication operator that receives a $1 \times N$ matrix Y_{n-k} from the unit delay operator and multiplies it with the $N \times 1$ matrix of scaled vector error data $(Z_n - X_n)$ to generate a $N \times N$ adjustment matrix;
- a matrix summation operator that adds the adjustment matrix to a Q_{n-k} tap matrix and outputs a corrected tap matrix Q_{n-k+1} ;
- matrix tap unit delay operator that receives the corrected tap matrix Q_{n-k+1} , and introduces a one cycle delay to generate a Q_{n-k} tap matrix; and
- a second matrix multiplication operator that multiplies the Q_{n-k} tap matrix from the matrix tap unit delay operator by the Y_{n-k+1} vector from the vector data unit delay operator.

SCANNED, # 22




FIG. 1




FIG. 1a




Figure 2a.




Figure 3 – A single tap of 4D-EQLFXC




Figure 4 – A single tap of 1D-EQL




Fig. 5a




Fig. 5b

4D-EQLFXC simulation
($N=20$, $\mu=0.01$)

4 1D-EQLs Simulation




FIG. 6a
PRIOR
ART

4 1D-EQLs Simulation




FIG. 6b
PRIOR
ART

4 1D-EQLs simulation

($N = 50$, $\mu = 0.01$)

DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below adjacent to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of subject matter (process, machine, manufacture, or composition of matter, or an improvement thereof) which is claimed and for which a patent is sought by way of the application entitled

Four Dimensional Equalizer and Far-End Cross Talk Canceler In Gigabit Ethernet Signals

which (check) ☒ is attached hereto.
☐ and is amended by the Preliminary Amendment attached hereto.
☐ was filed on as Application Serial No.
☐ and was amended on (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information, which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, § 119(a)-(d) of any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed:

Prior Foreign Application(s)			Priority Claimed	
Number	Country	Day/Month/Year Filed	Yes	No
N/A	{Country}		<input type="checkbox"/>	<input type="checkbox"/>

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below:

Provisional Application Number	Filing Date
N/A	

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) or PCT international application(s) designating the United States of America listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information, which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56, which became available between the filing date of the prior application(s) and the national or PCT international filing date of this application:

Application Serial No.	Filing Date	Status (patented, pending, abandoned)
N/A		{Status}

Alan H. MacPherson (24,423); Brian D. Ogonowsky (31,988); David W. Heid (25,875); Norman R. Klivans (33,003); Edward C. Kwok (33,938); David E. Steuber (25,557); Michael Shenker (34,250); Stephen A. Terrile (32,946); Peter H. Kang (40,350); Ronald J. Meetin (29,089); Ken John Koestner (33,004); Omkar K. Suryadevara (36,320); David T. Millers (37,396); Michael P. Adams (34,763); Robert B. Morrill (43,817); James E. Parsons (34,691); Philip W. Woo (39,880); Emily Haliday (38,903); Tom Hunter (38,498); Michael J. Halbert (40,633); Gary J. Edwards (41,008); Daniel P. Stewart (41,332); Tom Chen (42,406); Fabio E. Marino (43,339); Don C. Lawrence (31,975); Marc R. Ascolese (42,268); Carmen C. Cook (42,433); David G. Dolezal (41,711); Roberta P. Saxon (43,087); Mary Jo Bertani (42,321); Dale R. Cook (42,434); Sam G. Campbell (42,381); Matthew J. Brigham (44,047); Shireen Irani Bacon (40,494); Rory G. Bens (44,028); George Wolken, Jr. (30,441); John A. Odozynski (28,769); Paul E. Lewkowicz (44,870); Theodore P. Lopez (44,881); Eric Stephenson (38,321); Christopher Allenby (45,906); David C. Hsia (46,235); Mark J. Rozman (42,117); Margaret M. Kelton (44,182); Do Te Kim (46,231); Alex Chen (45,591); Monique M. Heyninck (44,763); Gregory J. Michelson (44,940); Jonathan Geld (44,702); Emmanuel Rivera (45,760); Jason FarHadian (42,523); Matthew J. Spark (43,453); Elaine H. Lo (41,158); Jon Hallman (42,622); Robert Strawbrich (36,692); Rita M. Wisor (41,382); Gregory Powell (47,005); and Mark E. Schmidt (47,063).

Mary Jo Bertani
SKJERVEN MORRILL MacPHERSON LLP
 25 Metro Drive, Suite 700
 San Jose, California 95110-1349

I declare that all statements made herein of my own knowledge are true, all statements made herein on information and belief are believed to be true, and all statements made herein are made with the knowledge that whoever, in any matter within the jurisdiction of the Patent and Trademark Office, knowingly and willfully falsifies, conceals, or covers up by any trick, scheme, or device a material fact, or makes any false, fictitious or fraudulent statements or representations, or makes or uses any false writing or document knowing the same to contain any false, fictitious or fraudulent statement or entry, shall be subject to the penalties including fine or imprisonment or both as set forth under 18 U.S.C. 1001, and that violations of this paragraph may jeopardize the validity of the application or this document, or the validity or enforceability of any patent, trademark registration, or certificate resulting therefrom.

Inventor's Signature:

Post Office Address: 4307 Renaissance Drive
San Jose, California 95134

Citizenship: Japan

Inventor's Signature:	_____	Date:	_____
Residence:	Sunnyvale, California		
Post Office Address:	1206 Susan Way	Citizenship:	Taiwan
	Sunnyvale, California 94087		

Inventor's Signature:		Date:	
Residence:	San Jose, California		
Post Office Address:	6618 Whitbourne Drive San Jose, California 95120	Citizenship:	United States